


# Lecture 3 - Back Propagation

DD2424

March 24, 2017

# Classification functions we have encountered so far

## Linear with 1 output




Input:  $\mathbf{x}$

Output:  $s = \mathbf{w}^T \mathbf{x} + b$

Final decision:

$$g(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x} + b)$$

## Linear with multiple outputs



Input:  $\mathbf{x}$


Output:  $\mathbf{s} = W\mathbf{x} + \mathbf{b}$

Final decision:

$$g(\mathbf{x}) = \arg \max_j s_j$$


# Classification functions we have encountered so far

## Linear with multiple probabilistic outputs



Final decision:  $g(\mathbf{x}) = \arg \max_j p_j$


# Computational graph of the multiple linear function



The computational graph:

- Represents order of computations.
- Displays the dependencies between the computed quantities.
- User input, parameters that have to be learnt.


Computational Graph helps automate gradient computations.



- Assume have labelled training data  $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$
- Set  $W, \mathbf{b}$  so they correctly & robustly predict labels of the  $\mathbf{x}_i$ 's
- Need then to
  1. Measure the quality of the prediction's based on  $W, \mathbf{b}$ .
  2. Find the optimal  $W, \mathbf{b}$  relative to the quality measure on the training data.


# Quality measures a.k.a. loss functions we've encountered

## Multi-class SVM loss




$$l_{\text{SVM}}(\mathbf{s}, y) = \sum_{\substack{j=1 \\ j \neq y}}^C \max(0, s_j - s_y + 1)$$

## Cross-entropy loss




$$l_{\text{c-e}}(\mathbf{p}, y) = -\log(p_y)$$

## Classification function




## Classification function




# Computational graph of the complete loss function

- Linear scoring function + SOFTMAX + cross-entropy loss




where  $y$  is the 1-hot response vector induced by the label  $y$ .

- Linear scoring function + multi-class SVM loss




# How do we learn $W, \mathbf{b}$ ?



- Assume have labelled training data  $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$
- Set  $W, \mathbf{b}$  so they correctly & robustly predict labels of the  $\mathbf{x}_i$ 's
- Need then to
  1. measure the quality of the prediction's based on  $W, \mathbf{b}$ .
  2. find an optimal  $W, \mathbf{b}$  relative to the quality measure on the training data.



# How do we learn $W, \mathbf{b}$ ?




- Let  $l$  be the loss function defined by the computational graph.
- Find  $W, \mathbf{b}$  by optimizing

$$\arg \max_{W, \mathbf{b}} \frac{1}{|\mathcal{D}|} \sum_{(\mathbf{x}, y) \in \mathcal{D}} l(\mathbf{x}, y, W, \mathbf{b})$$

- Solve using a variant of **mini-batch gradient descent**  
 $\implies$  need to efficiently compute the gradient vectors

$$\nabla_W l(\mathbf{x}, y, W, \mathbf{b})|_{(\mathbf{x}, y) \in \mathcal{D}} \quad \text{and} \quad \nabla_{\mathbf{b}} l(\mathbf{x}, y, W, \mathbf{b})|_{(\mathbf{x}, y) \in \mathcal{D}}$$

# How do we compute these gradients?




- Let  $l$  be the complete loss function defined by the computational graph.
- How do we efficiently compute the gradient vectors

$$\nabla_W l(\mathbf{x}, y, W, \mathbf{b})|_{(\mathbf{x}, y) \in \mathcal{D}} \quad \text{and} \quad \nabla_{\mathbf{b}} l(\mathbf{x}, y, W, \mathbf{b})|_{(\mathbf{x}, y) \in \mathcal{D}}?$$

- Answer: **Back Propagation**

# Today's lecture: Gradient computations in neural networks

- For our learning approach need to be able to compute gradients efficiently.
- BackProp is algorithm for achieving given the form of many of our classifiers and loss functions.



- BackProp relies on the **chain rule** applied to the **composition of functions**.
- Example: the composition of functions

$$l(\mathbf{x}, y, W, \mathbf{b}) = -\log(\mathbf{y}^T \text{softmax}(W\mathbf{x} + \mathbf{b}))$$

**linear classifier** then **SOFTMAX** then **CROSS-ENTROPY LOSS**

Chain Rule for functions with a scalar input and a scalar output

# Differentiation of the composition of functions

- Have two functions  $g : \mathbb{R} \rightarrow \mathbb{R}$  and  $f : \mathbb{R} \rightarrow \mathbb{R}$ .
- Define  $h : \mathbb{R} \rightarrow \mathbb{R}$  as the composition of  $f$  and  $g$ :

$$h(x) = (f \circ g)(x) = f(g(x))$$

- How do we compute

$$\frac{dh(x)}{dx} ?$$

- Use the chain rule.

- Have functions  $f, g : \mathbb{R} \rightarrow \mathbb{R}$  and define  $h : \mathbb{R} \rightarrow \mathbb{R}$  as

$$h(x) = (f \circ g)(x) = f(g(x))$$

- Derivative of  $h$  w.r.t.  $x$  is given by the Chain Rule.

- **Chain Rule**

$$\frac{dh(x)}{dx} = \frac{df(y)}{dy} \frac{dg(x)}{dx} \quad \text{where } y = g(x)$$

# Example of the Chain Rule in action

- Have

$$g(x) = x^2, \quad f(x) = \sin(x)$$

- One composition of these two functions is

$$h(x) = f(g(x)) = \sin(x^2)$$

- According to the **chain rule**

$$\begin{aligned} \frac{dh(x)}{dx} &= \frac{df(y)}{dy} \frac{dg(x)}{dx} \quad \leftarrow \text{where } y = x^2 \\ &= \frac{d \sin(y)}{dy} \frac{dx^2}{dx} \\ &= \cos(y) 2x \\ &= 2x \cos(x^2) \quad \leftarrow \text{plug in } y = x^2 \end{aligned}$$

# The composition of $n$ functions

- Have functions  $f_1, \dots, f_n : \mathbb{R} \rightarrow \mathbb{R}$
- Define function  $h : \mathbb{R} \rightarrow \mathbb{R}$  as the composition of  $f_j$ 's

$$h(x) = (f_n \circ f_{n-1} \circ \dots \circ f_1)(x) = f_n(f_{n-1}(\dots(f_1(x))\dots))$$

- Can we compute the derivative

$$\frac{dh(x)}{dx} \quad ?$$

- Yes recursively apply the CHAIN RULE



# The composition of $n$ functions

- Have functions  $f_1, \dots, f_n : \mathbb{R} \rightarrow \mathbb{R}$
- Define function  $h : \mathbb{R} \rightarrow \mathbb{R}$  as the composition of  $f_j$ 's

$$h(x) = (f_n \circ f_{n-1} \circ \dots \circ f_1)(x) = f_n(f_{n-1}(\dots(f_1(x))\dots))$$

- Can we compute the derivative

$$\frac{dh(x)}{dx} \quad ?$$

- Yes recursively apply the CHAIN RULE

# The Chain Rule for the composition of $n$ functions

$$h(x) = (f_n \circ f_{n-1} \circ \cdots \circ f_1)(x)$$

- Define

$$g_j = f_n \circ f_{n-1} \circ \cdots \circ f_j$$

- Therefore  $g_1 = h$ ,  $g_n = f_n$  and

$$g_j = g_{j+1} \circ f_j \quad \text{for } j = 1, \dots, n-1$$

- Let  $y_j = f_j(y_{j-1})$  and  $y_0 = x$  then

$$y_n = g_j(y_{j-1}) \quad \text{for } j = 1, \dots, n$$

- Apply the **Chain Rule**:

- For  $j = 1, 2, 3, \dots, n-1$

$$\begin{aligned} \frac{dy_n}{dy_{j-1}} &= \frac{dg_j(y_{j-1})}{dy_{j-1}} = \frac{d(g_{j+1} \circ f_j)(y_{j-1})}{dy_{j-1}} = \frac{dg_{j+1}(y_j)}{dy_j} \frac{df_j(y_{j-1})}{dy_{j-1}} \\ &= \frac{dy_n}{dy_j} \frac{dy_j}{dy_{j-1}} \end{aligned}$$

# The Chain Rule for the composition of $n$ functions

Recursively applying this fact gives:

$$\begin{aligned}\frac{dh(x)}{dx} &= \frac{dg_1(x)}{dx} && \leftarrow \text{Apply } h = g_1 \\ &= \frac{d(g_2 \circ f_1)(x)}{dx} && \leftarrow \text{Apply } g_1 = g_2 \circ f_1 \\ &= \frac{dg_2(y_1)}{dy_1} \frac{df_1(x)}{dx} && \leftarrow \text{Apply chain rule \& } y_1 = f_1(x) \\ &= \frac{d(g_3 \circ f_2)(y_1)}{dy_1} \frac{df_1(x)}{dx} && \leftarrow \text{Apply } g_2 = g_3 \circ f_2 \\ &= \frac{dg_3(y_2)}{dy_2} \frac{df_2(y_1)}{dy_1} \frac{df_1(x)}{dx} && \leftarrow \text{Apply chain rule \& } y_2 = f_2(y_1) \\ &\quad \vdots \\ &= \frac{dg_n(y_{n-1})}{dy_{n-1}} \frac{df_{n-1}(y_{n-2})}{dy_{n-2}} \dots \frac{df_2(y_1)}{dy_1} \frac{df_1(x)}{dx} \\ &= \frac{df_n(y_{n-1})}{dy_{n-1}} \frac{df_{n-1}(y_{n-2})}{dy_{n-2}} \dots \frac{df_2(y_1)}{dy_1} \frac{df_1(x)}{dx} && \leftarrow \text{Apply } g_n = f_n\end{aligned}$$

where  $y_j = (f_j \circ f_{j-1} \circ \dots \circ f_1)(x) = f_j(y_{j-1})$ .

# Summary: Chain Rule for a composition of $n$ functions

- Have  $f_1, \dots, f_n : \mathbb{R} \rightarrow \mathbb{R}$  and define  $h$  as their composition

$$h(x) = (f_n \circ f_{n-1} \circ \dots \circ f_1)(x)$$

- Then

$$\begin{aligned} \frac{dh(x)}{dx} &= \frac{df_n(y_{n-1})}{dy_{n-1}} \frac{df_{n-1}(y_{n-2})}{dy_{n-2}} \dots \frac{df_2(y_1)}{dy_1} \frac{df_1(x)}{dx} \\ &= \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_2}{dy_1} \frac{dy_1}{dx} \end{aligned}$$

where  $y_j = (f_j \circ f_{j-1} \circ \dots \circ f_1)(x) = f_j(y_{j-1})$ .

- **Remember:** As  $y_0 = x$  then for  $j = n-1, n-2, \dots, 0$

$$\frac{dy_n}{dy_j} = \frac{dy_n}{dy_{j+1}} \frac{dy_{j+1}}{dy_j}$$

# Summary: Chain Rule for a composition of $n$ functions

- Have  $f_1, \dots, f_n : \mathbb{R} \rightarrow \mathbb{R}$  and define  $h$  as their composition

$$h(x) = (f_n \circ f_{n-1} \circ \dots \circ f_1)(x)$$

- Then

$$\begin{aligned} \frac{dh(x)}{dx} &= \frac{df_n(y_{n-1})}{dy_{n-1}} \frac{df_{n-1}(y_{n-2})}{dy_{n-2}} \dots \frac{df_2(y_1)}{dy_1} \frac{df_1(x)}{dx} \\ &= \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_2}{dy_1} \frac{dy_1}{dx} \end{aligned}$$

where  $y_j = (f_j \circ f_{j-1} \circ \dots \circ f_1)(x) = f_j(y_{j-1})$ .

- **Remember:** As  $y_0 = x$  then for  $j = n - 1, n - 2, \dots, 0$

$$\frac{dy_n}{dy_j} = \frac{dy_n}{dy_{j+1}} \frac{dy_{j+1}}{dy_j}$$

# Exploit structure to compute gradient

$$\frac{dh(x)}{dx} = \frac{dy_n}{dx} = \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_2}{dy_1} \frac{dy_1}{dx}$$

Computation of  $\frac{dy_n}{dx}$  relies on:

- **Record keeping:** Compute and record values of the  $y_j$ 's.
- **Iteratively aggregate** local gradients.

For  $j = n - 1, n, \dots, 1$

- Compute local derivative:  $\frac{df_{j+1}(y_j)}{dy_j} = \frac{dy_{j+1}}{dy_j}$
- Aggregate:

$$\frac{dy_n}{dy_j} = \frac{dy_n}{dy_{j+1}} \frac{dy_{j+1}}{dy_j}$$

Remember  $\frac{dy_n}{dy_{j+1}} = \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_{j+2}}{dy_{j+1}}$

This is Backprop algorithm given a chain dependency between the  $y_j$ 's.

# Exploit structure to compute gradient

$$\frac{dh(x)}{dx} = \frac{dy_n}{dx} = \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_2}{dy_1} \frac{dy_1}{dx}$$

Computation of  $\frac{dy_n}{dx}$  relies on:

- **Record keeping:** Compute and record values of the  $y_j$ 's.
- **Iteratively aggregate** local gradients.

For  $j = n - 1, n, \dots, 1$

- Compute local derivative:  $\frac{df_{j+1}(y_j)}{dy_j} = \frac{dy_{j+1}}{dy_j}$

- Aggregate:

$$\frac{dy_n}{dy_j} = \frac{dy_n}{dy_{j+1}} \frac{dy_{j+1}}{dy_j}$$

Remember  $\frac{dy_n}{dy_{j+1}} = \frac{dy_n}{dy_{n-1}} \frac{dy_{n-1}}{dy_{n-2}} \dots \frac{dy_{j+2}}{dy_{j+1}}$

This is Backprop algorithm given a chain dependency between the  $y_j$ 's.

# Compute gradient of $h$ at a point $x^*$

$$h(x) = (f_n \circ f_{n-1} \circ \cdots \circ f_1)(x)$$


- Have a value for  $x = x^*$
- Want to (efficiently) compute

$$\left. \frac{dh(x)}{dx} \right|_{x=x^*}$$

- Use the **Back-Propagation** algorithm.
- It consists of a **Forward** and **Backward** pass.



# Back-Propagation for chains: Forward Pass




Evaluate  $h(x^*)$  and keep track of the intermediary results

- Compute  $y_1^* = f_1(x^*)$ .
- for  $j = 2, 3, \dots, n$

$$y_j^* = f_j(y_{j-1}^*)$$

- Keep a record of  $y_1^*, \dots, y_n^*$ .


# Back-Propagation for chains: Backward Pass



Compute local  $f_j$  gradients and aggregate:

- Set  $g = 1$ .
- for  $j = n, n - 1, \dots, 2$


$$g = g \times \left. \frac{df_j(y_{j-1})}{dy_{j-1}} \right|_{y_{j-1}=y_{j-1}^*}$$



**Note:**  $g = \left. \frac{dy_n}{dy_{j-1}} \right|_{y_{j-1}=y_{j-1}^*}$

- Then  $\left. \frac{dh(x)}{dx} \right|_{x=x^*} = g \times \left. \frac{df_1(x)}{dx} \right|_{x=x^*}$


# Problem 1: But what if I don't have a chain?



- This computational graph is **not a chain**.
- Some nodes have multiple parents.
- The function represented by graph is

$$l(\mathbf{x}, \mathbf{y}, W, \mathbf{b}) = -\log(\mathbf{y}^T \text{Softmax}(W\mathbf{x} + \mathbf{b}))$$

# Problem 1a: And when a regularization term is added..




- This computational graph is **not a chain**.
- Some nodes have **multiple parents** and others **multiple children**.
- The function represented by graph is

$$J(\mathbf{x}, \mathbf{y}, W, \mathbf{b}, \lambda) = -\log(\mathbf{y}^T \text{Softmax}(W\mathbf{x} + \mathbf{b})) + \lambda \sum_{i,j} W_{i,j}^2$$

- How is the back-propagation algorithm defined in these cases?

# Problem 1a: And when a regularization term is added..




- This computational graph is **not a chain**.
- Some nodes have **multiple parents** and others **multiple children**.
- The function represented by graph is

$$J(\mathbf{x}, \mathbf{y}, W, \mathbf{b}, \lambda) = -\log(\mathbf{y}^T \text{Softmax}(W\mathbf{x} + \mathbf{b})) + \lambda \sum_{i,j} W_{i,j}^2$$

- How is the back-propagation algorithm defined in these cases?


## Problem 2: Don't have scalar inputs and outputs




- The function represented by graph:

$$J(\mathbf{x}, \mathbf{y}, W, \mathbf{b}, \lambda) = -\log(\mathbf{y}^T \text{Softmax}(W\mathbf{x} + \mathbf{b})) + \lambda \sum_{i,j} W_{i,j}^2$$

- Nearly all of the inputs and intermediary outputs are **vectors** or **matrices**.
- How are the derivatives defined in this case?



- Back-propagation when the computational graph is **not a chain**.
- Derivative computations when the inputs and outputs are not scalars.
- Will address these issues now. First the derivatives of vectors.



- Back-propagation when the computational graph is **not a chain**.
- Derivative computations when the inputs and outputs are not scalars.
- **Will address these issues now.** First the derivatives of vectors.



Chain Rule for functions with vector inputs and vector outputs

# Chain Rule for vector input and output

- Have two functions  $g : \mathbb{R}^d \rightarrow \mathbb{R}^m$  and  $f : \mathbb{R}^m \rightarrow \mathbb{R}^c$ .
- Define  $h : \mathbb{R}^d \rightarrow \mathbb{R}^c$  as the composition of  $f$  and  $g$ :

$$h(\mathbf{x}) = (f \circ g)(\mathbf{x}) = f(g(\mathbf{x}))$$

- Consider

$$\frac{\partial h(\mathbf{x})}{\partial \mathbf{x}}$$

- How is it defined and computed?
- What's the chain rule for vector valued functions?

# Chain Rule for vector input and output

- Let  $\mathbf{y} = h(\mathbf{x})$  where each  $h : \mathbb{R}^d \rightarrow \mathbb{R}^c$  then

$$\frac{\partial h(\mathbf{x})}{\partial \mathbf{x}} = \frac{\partial \mathbf{y}}{\partial \mathbf{x}} = \begin{pmatrix} \frac{\partial y_1}{\partial x_1} & \cdots & \frac{\partial y_1}{\partial x_d} \\ \frac{\partial y_2}{\partial x_1} & \cdots & \frac{\partial y_2}{\partial x_d} \\ \vdots & \vdots & \vdots \\ \frac{\partial y_c}{\partial x_1} & \cdots & \frac{\partial y_c}{\partial x_d} \end{pmatrix} \quad \leftarrow \text{this is a Jacobian matrix}$$

and is a matrix of size  $c \times d$ .

- Chain Rule** says if  $h = f \circ g$  ( $g : \mathbb{R}^d \rightarrow \mathbb{R}^m$  and  $f : \mathbb{R}^m \rightarrow \mathbb{R}^c$ ) then

$$\frac{\partial h(\mathbf{x})}{\partial \mathbf{x}} = \frac{\partial \mathbf{y}}{\partial \mathbf{x}} = \frac{\partial \mathbf{y}}{\partial \mathbf{z}} \frac{\partial \mathbf{z}}{\partial \mathbf{x}}$$

where  $\mathbf{z} = g(\mathbf{x})$  and  $\mathbf{y} = f(\mathbf{z})$ .

- Both  $\frac{\partial \mathbf{y}}{\partial \mathbf{z}}$  ( $c \times m$ ) and  $\frac{\partial \mathbf{z}}{\partial \mathbf{x}}$  ( $m \times d$ ) defined sllly to  $\frac{\partial \mathbf{y}}{\partial \mathbf{x}}$ .

# Chain Rule for vector input and scalar output

The cost functions we will examine usually have a scalar output

- Let  $\mathbf{x} \in \mathbb{R}^d$ ,  $f : \mathbb{R}^d \rightarrow \mathbb{R}^m$  and  $g : \mathbb{R}^m \rightarrow \mathbb{R}$

$$\mathbf{z} = f(\mathbf{x})$$

$$s = g(\mathbf{z})$$

- The **Chain Rule** says gradient of output w.r.t. input

$$\frac{\partial s}{\partial \mathbf{x}} = \left( \frac{\partial s}{\partial x_1} \quad \cdots \quad \frac{\partial s}{\partial x_d} \right)$$

is given by a gradient times a Jacobian:

$$\frac{\partial s}{\partial \mathbf{x}} = \underbrace{\frac{\partial s}{\partial \mathbf{z}}}_{1 \times m} \underbrace{\frac{\partial \mathbf{z}}{\partial \mathbf{x}}}_{m \times d}$$

where

$$\frac{\partial \mathbf{z}}{\partial \mathbf{x}} = \begin{pmatrix} \frac{\partial z_1}{\partial x_1} & \cdots & \frac{\partial z_1}{\partial x_d} \\ \frac{\partial z_2}{\partial x_1} & \cdots & \frac{\partial z_2}{\partial x_d} \\ \vdots & \vdots & \vdots \\ \frac{\partial z_m}{\partial x_1} & \cdots & \frac{\partial z_m}{\partial x_d} \end{pmatrix}$$

# Two intermediary vector inputs and scalar output

- $f_1 : \mathbb{R}^d \rightarrow \mathbb{R}^{m_1}$ ,  $f_2 : \mathbb{R}^d \rightarrow \mathbb{R}^{m_2}$  and  $g : \mathbb{R}^n \rightarrow \mathbb{R}$  ( $n = m_1 + m_2$ )

$$\mathbf{z}_1 = f_1(\mathbf{x}),$$

$$\mathbf{z}_2 = f_2(\mathbf{x})$$

$$s = g(\mathbf{z}_1, \mathbf{z}_2) = g(\mathbf{v}) \quad \text{where } \mathbf{v} = \begin{pmatrix} \mathbf{z}_1 \\ \mathbf{z}_2 \end{pmatrix}.$$

- **Chain Rule** says gradient of the output w.r.t. the input

$$\frac{\partial s}{\partial \mathbf{x}} = \left( \frac{\partial s}{\partial x_1} \quad \cdots \quad \frac{\partial s}{\partial x_d} \right)$$

is given by:

$$\frac{\partial s}{\partial \mathbf{x}} = \underbrace{\frac{\partial s}{\partial \mathbf{v}}}_{1 \times n} \underbrace{\frac{\partial \mathbf{v}}{\partial \mathbf{x}}}_{n \times d}$$

But

$$\frac{\partial s}{\partial \mathbf{v}} = \left( \frac{\partial s}{\partial \mathbf{z}_1} \quad \frac{\partial s}{\partial \mathbf{z}_2} \right) \quad \text{and} \quad \frac{\partial \mathbf{v}}{\partial \mathbf{x}} = \begin{pmatrix} \frac{\partial \mathbf{z}_1}{\partial \mathbf{x}} \\ \frac{\partial \mathbf{z}_2}{\partial \mathbf{x}} \end{pmatrix}$$

$\implies$

$$\frac{\partial s}{\partial \mathbf{x}} = \frac{\partial s}{\partial \mathbf{v}} \frac{\partial \mathbf{v}}{\partial \mathbf{x}} = \underbrace{\frac{\partial s}{\partial \mathbf{z}_1}}_{1 \times m_1} \underbrace{\frac{\partial \mathbf{z}_1}{\partial \mathbf{x}}}_{m_1 \times d} + \underbrace{\frac{\partial s}{\partial \mathbf{z}_2}}_{1 \times m_2} \underbrace{\frac{\partial \mathbf{z}_2}{\partial \mathbf{x}}}_{m_2 \times d}$$

- $f_i : \mathbb{R}^d \rightarrow \mathbb{R}^{m_i}$  for  $i = 1, \dots, t$  and  $g : \mathbb{R}^n \rightarrow \mathbb{R}$  ( $n = m_1 + \dots + m_t$ )

$$\mathbf{z}_i = f_i(\mathbf{x}), \quad \text{for } i = 1, \dots, t$$


$$s = g(\mathbf{z}_1, \dots, \mathbf{z}_n)$$


- Consequence of the **Chain Rule**

$$\frac{\partial s}{\partial \mathbf{x}} = \sum_{i=1}^t \frac{\partial s}{\partial \mathbf{z}_i} \frac{\partial \mathbf{z}_i}{\partial \mathbf{x}}$$

- Computational graph interpretation. Let  $\mathcal{C}_s$  be the children nodes of  $s$  then

$$\frac{\partial s}{\partial \mathbf{x}} = \sum_{\mathbf{z} \in \mathcal{C}_s} \frac{\partial s}{\partial \mathbf{z}} \frac{\partial \mathbf{z}}{\partial \mathbf{x}}$$






- Back-propagation when the computational graph is **not a chain**.
- Derivative computations when the inputs and outputs are not scalars. ✓
- Will now describe Back-prop for non-chains.

Back-propagation for non-chain computational graphs



- Have node  $y$ .
- Denote the set of  $y$ 's children nodes by  $\mathcal{C}_y$  and their values by


$$V_{\mathcal{C}_y} = \{z.\text{value} \mid z \in \mathcal{C}_y\}$$



- Given  $V_{\mathcal{C}_y}$  can now apply the function  $f_z$

$$y.\text{value} = f_y(V_{\mathcal{C}_y})$$

# Results that we need but already know



- Consider node  $W$  in the above graph. Its children are  $\{z, r\}$ . Applying the chain rule

$$\frac{\partial J}{\partial W} = \frac{\partial J}{\partial r} \frac{\partial r}{\partial W} + \frac{\partial J}{\partial z} \frac{\partial z}{\partial W}$$

- In general for node  $c$  with children specified by  $\mathcal{C}_c$ :

$$\frac{\partial J}{\partial c} = \sum_{u \in \mathcal{C}_c} \frac{\partial J}{\partial u} \frac{\partial u}{\partial c}$$

# Pseudo-Code for the Generic Forward Pass

**procedure** EVALUATEGRAHPFN( $G$ )

$\mathcal{S} = \text{GetStartNodes}(G)$

**for**  $s \in \mathcal{S}$  **do**

        ComputeBranch( $s, G$ )

**end for**

**end procedure**

▷  $G$  is the computational graph

▷ a start node has no children and its value is already set

**procedure** COMPUTEBRANCH( $s, G$ )

$\mathcal{P}_s = \text{GetParents}(s, G)$

**for each**  $n \in \mathcal{P}_s$  **do**

**if** ! $n$ .computed **then**

$\mathcal{C}_n = \text{GetChildren}(n, G)$

**if** CheckAllNodesComputed( $\mathcal{C}_n$ ) **then** ▷ Or not all children of parent are computed

$f_n = \text{GetNodeFn}(n)$

$n$ .value =  $f_n(\mathcal{C}_n)$

$n$ .computed = true

                ComputeBranch( $n, G$ )

**end if**

**end if**

**end for**


**end procedure**

▷ recursive fn evaluating nodes

▷ Try to evaluate each parent node

▷ Unless parent is already computed

## Identify Start Nodes




```

procedure EVALUATEGRAPHFN( $G$ )  ▷  $G$  is the computational graph
   $S = \text{GetStartNodes}(G)$ 
  for  $s \in S$  do
     $\text{ComputeBranch}(s, G)$ 
  end for
end procedure
    
```

```

procedure COMPUTEBRANCH( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$ 
  for each  $n \in \mathcal{P}_s$  do
    if ! $n$ .computed then
       $C_n = \text{GetChildren}(n, G)$ 
      if  $\text{CheckAllNodesComputed}(C_n)$  then
         $f_n = \text{GetNodeFn}(n)$ 
         $n$ .value =  $f_n(C_n)$ 
         $n$ .computed = true
         $\text{ComputeBranch}(n, G)$ 
      end if
    end if
  end for
end procedure
    
```

## Order in which nodes are evaluated



```

procedure EVALUATEGRAPHFN( $G$ )  $\triangleright G$  is the computational graph
   $S = \text{GetStartNodes}(G)$ 
  for  $s \in S$  do
     $\text{ComputeBranch}(s, G)$ 
  end for
end procedure


```

```

procedure COMPUTEBRANCH( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$ 
  for each  $n \in \mathcal{P}_s$  do
    if  $\neg n.\text{computed}$  then
       $C_n = \text{GetChildren}(n, G)$ 
      if  $\text{CheckAllNodesComputed}(C_n)$  then
         $f_n = \text{GetNodeFn}(n)$ 
         $n.\text{value} = f_n(C_n)$ 
         $n.\text{computed} = \text{true}$ 
         $\text{ComputeBranch}(n, G)$ 
      end if
    end if
  end for
end procedure

```

## Order in which nodes are evaluated




```

procedure EVALUATEGRAPHFN(G) ▷ G is the computational graph
  S = GetStartNodes(G)
  for s ∈ S do
    ComputeBranch(s, G)
  end for
end procedure
  
```

```

procedure COMPUTEBRANCH(s, G)
  Ps = GetParents(s, G)
  for each n ∈ Ps do
    if !n.computed then
      Cn = GetChildren(n, G)
      if CheckAllNodesComputed(Cn) then
        fn = GetNodeFn(n)
        n.value = fn(Cn)
        n.computed = true
        ComputeBranch(n, G)
      end if
    end if
  end for
end procedure
  
```

## Order in which nodes are evaluated



```

procedure EVALUATEGRAPHFN( $G$ )  $\triangleright G$  is the computational graph
   $S = \text{GetStartNodes}(G)$ 
  for  $s \in S$  do
     $\text{ComputeBranch}(s, G)$ 
  end for
end procedure


```

```

procedure COMPUTEBRANCH( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$ 
  for each  $n \in \mathcal{P}_s$  do
    if  $\neg n.\text{computed}$  then
       $C_n = \text{GetChildren}(n, G)$ 
      if  $\text{CheckAllNodesComputed}(C_n)$  then
         $f_n = \text{GetNodeFn}(n)$ 
         $n.\text{value} = f_n(C_n)$ 
         $n.\text{computed} = \text{true}$ 
         $\text{ComputeBranch}(n, G)$ 
      end if
    end if
  end for
end procedure

```

## Order in which nodes are evaluated



```


procedure EVALUATEGRAPHFN(G)  $\triangleright$  G is the computational graph
  S = GetStartNodes(G)
  for s  $\in$  S do
    ComputeBranch(s, G)
  end for
end procedure
  
```

```

procedure COMPUTEBRANCH(s, G)
  Ps = GetParents(s, G)
  for each n  $\in$  Ps do
    if !n.computed then
      Cn = GetChildren(n, G)
      if CheckAllNodesComputed(Cn) then
        fn = GetNodeFn(n)
        n.value = fn(Cn)
        n.computed = true
        ComputeBranch(n, G)
      end if
    end if
  end for
end procedure
  
```



## Order in which nodes are evaluated




```

procedure EVALUATEGRAPHFN(G) ▷ G is the computational graph
  S = GetStartNodes(G)
  for s ∈ S do
    ComputeBranch(s, G)
  end for
end procedure
  
```

```

procedure COMPUTEBRANCH(s, G)
  Ps = GetParents(s, G)
  for each n ∈ Ps do
    if !n.computed then
      Cn = GetChildren(n, G)
      if CheckAllNodesComputed(Cn) then
        fn = GetNodeFn(n)
        n.value = fn(Cn)
        n.computed = true
        ComputeBranch(n, G)
      end if
    end if
  end for
end procedure
  
```

## Order in which nodes are evaluated



```

procedure EVALUATEGRAPHFN(G) ▷ G is the computational graph
  S = GetStartNodes(G)
  for s ∈ S do
    ComputeBranch(s, G)
  end for
end procedure
  
```

```

procedure COMPUTEBRANCH(s, G)
  Ps = GetParents(s, G)
  for each n ∈ Ps do
    if !n.computed then
      Cn = GetChildren(n, G)
      if CheckAllNodesComputed(Cn) then
        fn = GetNodeFn(n)
        n.value = fn(Cn)
        n.computed = true
        ComputeBranch(n, G)
      end if
    end if
  end for
end procedure
  
```

# Pseudo-Code for the Generic Backward Pass

**procedure** PERFORMBACKPASS(G)

$J = \text{GetResultNode}(G)$

    BackOp( $J, G$ )

**end procedure**

▷ node with the value of cost function

▷ Start the Backward-pass

**procedure** BACKOP( $s, G$ )

$\mathcal{P}_s = \text{GetParents}(s, G)$

**if**  $\mathcal{P}_s = \emptyset$  **then**

$s.\text{Grad} = 1$

**end if**

**if** AllGradientsComputed( $\mathcal{P}_s$ ) **then**

$s.\text{Grad} = 0$

**for each**  $\mathbf{p} \in \mathcal{P}_s$  **do**

$s.\text{Grad} += \mathbf{p}.\text{Grad} * \mathbf{p}.s.\text{Jacobian}$

**end for**

$s.\text{GradComputed} = \text{true}$

**end if**

**for each**  $\mathbf{c} \in \mathcal{C}_s$  **do**

$s.c.\text{Jacobian} = \frac{\partial f_s(\mathcal{C}_s)}{\partial \mathbf{c}}$

        BackOp( $\mathbf{c}, G$ )

**end for**

**end procedure**

▷ At the result node

▷ Have computed all  $\frac{\partial J}{\partial \mathbf{p}}$  where  $\mathbf{p} \in \mathcal{P}_s$


▷  $\frac{\partial J}{\partial \mathbf{s}} += \frac{\partial J}{\partial \mathbf{p}} \frac{\partial \mathbf{p}}{\partial \mathbf{s}}$

▷ Compute the Jacobian of  $f_s$  w.r.t. each child node

▷  $\frac{\partial f_s(\mathcal{C}_s)}{\partial \mathbf{c}} = \frac{\partial \mathbf{s}}{\partial \mathbf{c}}$

# Generic Backward Pass: Order of computations

## Identify Result Node



```


procedure PERFORMBACKPASS(G)
   $J = \text{GetResultNode}(G)$   $\triangleright$  node with the value of the cost function
  BackOp( $J, G$ )  $\triangleright$  Start the Backward-pass
end procedure
  
```

```

procedure BACKOP( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$   $\triangleright$  At the result node
  if  $\mathcal{P}_s = \emptyset$  then
     $s.\text{Grad} = 1$ 
  else
    if AllGradientsComputed( $\mathcal{P}_s$ ) then  $\triangleright$  All  $\frac{\partial J}{\partial p}$  computed where  $p \in \mathcal{P}_s$ 
       $s.\text{Grad} = 0$ 
      for each  $p \in \mathcal{P}_s$  do
         $s.\text{Grad} += p.\text{Grad} * p.s.\text{Jacobian}$   $\triangleright \frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
       $s.\text{GradComputed} = \text{true}$ 
    end if
  end if
  for each  $c \in \mathcal{C}_s$  do  $\triangleright$  Compute Jacobian of  $f_s$  w.r.t. each child node
     $s.c.\text{Jacobian} = \frac{\partial f_s(C_s)}{\partial c}$   $\triangleright \frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp( $c, G$ )
  end for
end procedure
  
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of fs w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(c_c)}{\partial c}$  ▷  $\frac{\partial f_s(c_c)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
   $J = \text{GetResultNode}(G)$   $\triangleright$  node with the value of cost function
  BackOp( $J, G$ )  $\triangleright$  Start the Backward-pass
end procedure
  
```

```

procedure BACKOP( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$   $\triangleright$  At the result node
  if  $\mathcal{P}_s = \emptyset$  then
     $s.\text{Grad} = 1$ 
  else
    if AllGradientsComputed( $\mathcal{P}_s$ ) then  $\triangleright$  All  $\frac{\partial J}{\partial p}$  computed where  $p \in \mathcal{P}_s$ 
       $s.\text{Grad} = 0$ 
      for each  $p \in \mathcal{P}_s$  do
         $s.\text{Grad} += p.\text{Grad} * p.s.\text{Jacobian}$   $\triangleright \frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
       $s.\text{GradComputed} = \text{true}$ 
    end if
  end if
  for each  $c \in \mathcal{C}_s$  do  $\triangleright$  Compute Jacobian of  $f_s$  w.r.t. each child node
     $s.c.\text{Jacobian} = \frac{\partial f_s(C_s)}{\partial c}$   $\triangleright \frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp( $c, G$ )
  end for
end procedure
  
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS( $G$ )
   $J = \text{GetResultNode}(G)$   $\triangleright$  node with the value of cost function
  BackOp( $J, G$ )  $\triangleright$  Start the Backward-pass
end procedure
  
```

```

procedure BACKOP( $s, G$ )
   $\mathcal{P}_s = \text{GetParents}(s, G)$   $\triangleright$  At the result node
  if  $\mathcal{P}_s = \emptyset$  then
     $s.\text{Grad} = 1$ 
  else
    if AllGradientsComputed( $\mathcal{P}_s$ ) then  $\triangleright$  All  $\frac{\partial J}{\partial p}$  computed where  $p \in \mathcal{P}_s$ 
       $s.\text{Grad} = 0$ 
      for each  $p \in \mathcal{P}_s$  do
         $s.\text{Grad} += p.\text{Grad} * p.s.\text{Jacobian}$   $\triangleright \frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
       $s.\text{GradComputed} = \text{true}$ 
    end if
  end if
  for each  $c \in \mathcal{C}_s$  do  $\triangleright$  Compute Jacobian of  $f_s$  w.r.t. each child node
     $s.c.\text{Jacobian} = \frac{\partial f_s(C_s)}{\partial c}$   $\triangleright \frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp( $c, G$ )
  end for
end procedure
  
```

# Generic Backward Pass: Order of computations

Compute Jacobian of current node w.r.t. its child



```

procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```


```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```



# Generic Backward Pass: Order of computations

## Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then
    s.Grad = 1 ▷ At the result node
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where p ∈ Ps
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of fs w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All ∂J/∂p computed where p ∈ Ps
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷ ∂J/∂s += ∑ ∂J/∂p ∂p/∂s
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of fs w.r.t. each child node
    s.c.Jacobian = ∂fs(Cs) / ∂c ▷ ∂fs(Cs) / ∂c = ∂s/∂c
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
    for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
      s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
      BackOp(c, G)
    end for
  end procedure
    
```

# Generic Backward Pass: Order of computations

Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```

procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```


```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```



# Generic Backward Pass: Order of computations

## Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
  
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
  
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

Compute Jacobian of current node w.r.t. its child



```


procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```

procedure BACKOP(s, G)
  Ps = GetParents(s, G) ▷ At the result node
  if Ps = ∅ then
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
  end if
  for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
    s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
    BackOp(c, G)
  end for
end procedure
    
```

# Generic Backward Pass: Order of computations

## Compute Gradient of current node



$$\frac{\partial J}{\partial W} = \frac{\partial J}{\partial z} \frac{\partial z}{\partial W} + \frac{\partial J}{\partial r} \frac{\partial r}{\partial W}$$


$$\|W\|^2$$

```

procedure PERFORMBACKPASS(G)
  J = GetResultNode(G) ▷ node with the value of cost function
  BackOp(J, G) ▷ Start the Backward-pass
end procedure
    
```

```


procedure BACKOP(s, G)
  Ps = GetParents(s, G)
  if Ps = ∅ then ▷ At the result node
    s.Grad = 1
  else
    if AllGradientsComputed(Ps) then ▷ All  $\frac{\partial J}{\partial p}$  computed where  $p \in P_s$ 
      s.Grad = 0
      for each p ∈ Ps do
        s.Grad += p.Grad * p.s.Jacobian ▷  $\frac{\partial J}{\partial s} += \frac{\partial J}{\partial p} \frac{\partial p}{\partial s}$ 
      end for
      s.GradComputed = true
    end if
    end if
    for each c ∈ Cs do ▷ Compute Jacobian of  $f_s$  w.r.t. each child node
      s.c.Jacobian =  $\frac{\partial f_s(C_s)}{\partial c}$  ▷  $\frac{\partial f_s(C_s)}{\partial c} = \frac{\partial s}{\partial c}$ 
      BackOp(c, G)
    end for
  end procedure
    
```



- Back-propagation when the computational graph is **not a chain**. ✓
- Derivative computations when the inputs and outputs are not scalars. ✓
- Let's now compute some gradients!

# Example of the chain rule in action

Compute gradients for




**linear scoring function + SOFTMAX + cross-entropy loss +  
Regularization**

- Assume the forward pass has been completed.
- $\implies$  value for every node is known.

# Generic Backward Pass: Gradient of current node


## Compute Gradient of node $J$



$$\frac{\partial J}{\partial J} = 1$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $J$  w.r.t. its child  $r$




$$J = l + \lambda r$$

$$\frac{\partial J}{\partial r} = \lambda$$



# Generic Backward Pass: Order of computations

## Compute Gradient of node $r$




$$J = l + \lambda r$$

$$\frac{\partial J}{\partial r} = \frac{\partial J}{\partial J} \frac{\partial J}{\partial r} = \lambda$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $r$  w.r.t. its child  $W$




$$r = \sum_{i,j} W_{ij}^2$$

$$\frac{\partial r}{\partial W} = ?$$

Derivative of a scalar w.r.t. a matrix

# Generic Backward Pass: Compute Jacobian




$$r = \sum_{i,j} W_{ij}^2$$

- Jacobian to compute:  $\frac{\partial r}{\partial W} = \begin{pmatrix} \frac{\partial r}{\partial W_{11}} & \frac{\partial r}{\partial W_{12}} & \cdots & \cdots & \frac{\partial r}{\partial W_{1d}} \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ \frac{\partial r}{\partial W_{C1}} & \frac{\partial r}{\partial W_{C2}} & \cdots & \cdots & \frac{\partial r}{\partial W_{Cd}} \end{pmatrix}$
- The individual derivatives:  $\frac{\partial r}{\partial W_{ij}} = 2W_{ij}$
- Putting it together in matrix notation

$$\frac{\partial r}{\partial W} = 2W$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $J$  w.r.t. its child  $l$




$$J = l + \lambda r$$

$$\frac{\partial J}{\partial l} = 1$$

# Generic Backward Pass: Order of computations


## Compute Gradient of node $l$



$$\frac{\partial J}{\partial l} = \frac{\partial J}{\partial y} \frac{\partial y}{\partial l} = 1$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $l$  w.r.t. its child  $p$




$$l = -\log(\mathbf{y}^T \mathbf{p})$$

- The Jacobian we want to compute:  $\frac{\partial l}{\partial \mathbf{p}} = \left( \frac{\partial l}{\partial p_1}, \frac{\partial l}{\partial p_2}, \dots, \frac{\partial l}{\partial p_C} \right)$
- The individual derivatives:  $\frac{\partial l}{\partial p_i} = -\frac{y_i}{\mathbf{y}^T \mathbf{p}}$  for  $i = 1, \dots, C$
- Putting it together:

$$\frac{\partial l}{\partial \mathbf{p}} = -\frac{\mathbf{y}^T}{\mathbf{y}^T \mathbf{p}}$$

# Generic Backward Pass: Order of computations

## Compute Gradient of node p




$$l = -\log(\mathbf{y}^T \mathbf{p})$$

$$\frac{\partial J}{\partial \mathbf{p}} = \frac{\partial J}{\partial l} \frac{\partial l}{\partial \mathbf{p}}$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $p$  w.r.t. its child  $s$



- The Jacobian we need to compute:  $\frac{\partial \mathbf{p}}{\partial \mathbf{s}} = \begin{pmatrix} \frac{\partial p_1}{\partial s_1} & \dots & \frac{\partial p_1}{\partial s_C} \\ \vdots & \ddots & \vdots \\ \frac{\partial p_C}{\partial s_1} & \dots & \frac{\partial p_C}{\partial s_C} \end{pmatrix}$

- The individual derivatives:


$$\frac{\partial p_i}{\partial s_j} = \begin{cases} p_i(1 - p_i) & \text{if } i = j \\ -p_i p_j & \text{otherwise} \end{cases}$$

- Putting it together in vector notation:  $\frac{\partial \mathbf{p}}{\partial \mathbf{s}} = \text{diag}(\mathbf{p}) - \mathbf{p}\mathbf{p}^T$



# Generic Backward Pass: Order of computations

## Compute Gradient of node s




$$\mathbf{p} = \exp(\mathbf{s}) / (\mathbf{1}^T \exp(\mathbf{s}))$$

$$\frac{\partial J}{\partial \mathbf{s}} = \frac{\partial J}{\partial \mathbf{p}} \frac{\partial \mathbf{p}}{\partial \mathbf{s}}$$

# Generic Backward Pass: Order of computations


Compute Jacobian of node  $s$  w.r.t. its child  $b$



- The Jacobian we need to compute:  $\frac{\partial \mathbf{s}}{\partial \mathbf{b}} = \begin{pmatrix} \frac{\partial s_1}{\partial b_1} & \cdots & \frac{\partial s_1}{\partial b_C} \\ \vdots & \vdots & \vdots \\ \frac{\partial s_C}{\partial b_1} & \cdots & \frac{\partial s_C}{\partial b_C} \end{pmatrix}$
- The individual derivatives:  $\frac{\partial s_i}{\partial b_j} = \begin{cases} 1 & \text{if } i = j \\ 0 & \text{otherwise} \end{cases}$
- In vector notation:  $\frac{\partial \mathbf{s}}{\partial \mathbf{b}} = I_C \leftarrow \text{the identity matrix of size } C \times C$

# Generic Backward Pass: Order of computations

## Compute Gradient of node b




gradient needed for mini-batch g.d.training as  $\mathbf{b}$  parameter of the model  $\rightarrow$

$$\frac{\partial J}{\partial \mathbf{b}} = \frac{\partial J}{\partial \mathbf{s}} \frac{\partial \mathbf{s}}{\partial \mathbf{b}}$$

# Generic Backward Pass: Order of computations

## Compute Jacobian of node $s$ w.r.t. its child $z$




$$\mathbf{s} = \mathbf{z} + \mathbf{b}$$

- The Jacobian we need to compute:  $\frac{\partial \mathbf{s}}{\partial \mathbf{z}} = \begin{pmatrix} \frac{\partial s_1}{\partial z_1} & \cdots & \frac{\partial s_1}{\partial z_C} \\ \vdots & \vdots & \vdots \\ \frac{\partial s_C}{\partial z_1} & \cdots & \frac{\partial s_C}{\partial z_C} \end{pmatrix}$
- The individual derivatives:  $\frac{\partial s_i}{\partial z_j} = \begin{cases} 1 & \text{if } i = j \\ 0 & \text{otherwise} \end{cases}$
- In vector notation:  $\frac{\partial \mathbf{s}}{\partial \mathbf{z}} = I_C \leftarrow \text{the identity matrix of size } C \times C$

# Generic Backward Pass: Order of computations


## Compute Gradient of node z



$$\frac{\partial J}{\partial z} = \frac{\partial J}{\partial s} \frac{\partial s}{\partial z}$$

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $z$  w.r.t. its child  $W$



- No consistent definition for “Jacobian” of vector w.r.t. matrix.
- Instead re-arrange  $W$  ( $C \times d$ ) into a vector  $\text{vec}(W)$  ( $Cd \times 1$ )

$$W = \begin{pmatrix} \mathbf{w}_1^T \\ \mathbf{w}_2^T \\ \vdots \\ \mathbf{w}_C^T \end{pmatrix} \quad \text{then} \quad \text{vec}(W) = \begin{pmatrix} \mathbf{w}_1 \\ \mathbf{w}_2 \\ \vdots \\ \mathbf{w}_C \end{pmatrix}$$


- Then

$$\mathbf{z} = \left( I_C \otimes \mathbf{x}^T \right) \text{vec}(W)$$

where  $\otimes$  denotes the **Kronecker product** between two matrices.

# Generic Backward Pass: Order of computations

Compute Jacobian of node  $z$  w.r.t. its child  $W$




$$\mathbf{z} = W\mathbf{x} = (I_C \otimes \mathbf{x}^T) \text{vec}(W)$$

- Let  $\mathbf{v} = \text{vec}(W)$ . Jacobian to compute:  $\frac{\partial \mathbf{z}}{\partial \mathbf{v}} = \begin{pmatrix} \frac{\partial z_1}{\partial v_1} & \cdots & \frac{\partial z_1}{\partial v_{dC}} \\ \vdots & \vdots & \vdots \\ \frac{\partial z_C}{\partial v_1} & \cdots & \frac{\partial z_C}{\partial v_{dC}} \end{pmatrix}$
- The individual derivatives:  $\frac{\partial z_i}{\partial v_j} = \begin{cases} x_{j-(i-1)d} & \text{if } (i-1)d + 1 \leq j \leq id \\ 0 & \text{otherwise} \end{cases}$
- In vector notation:  $\frac{\partial \mathbf{z}}{\partial \mathbf{v}} = I_C \otimes \mathbf{x}^T$

# Generic Backward Pass: Order of computations

## Compute Gradient of node $W$



$$\mathbf{z} = W\mathbf{x} = (I_C \otimes \mathbf{x}^T) \text{vec}(W)$$

gradient needed for learning  $\rightarrow$


$$\begin{aligned} \frac{\partial J}{\partial \text{vec}(W)} &= \frac{\partial J}{\partial \mathbf{z}} \frac{\partial \mathbf{z}}{\partial \text{vec}(W)} + \frac{\partial J}{\partial r} \frac{\partial r}{\partial \text{vec}(W)} \\ &= (g_1 \mathbf{x}^T \quad g_2 \mathbf{x}^T \quad \dots \quad g_C \mathbf{x}^T) + 2\lambda \text{vec}(W)^T \end{aligned}$$

if we set  $\mathbf{g} = \frac{\partial J}{\partial \mathbf{z}}$ .



# Generic Backward Pass: Order of computations

## Compute Gradient of node $W$




Can convert

$$\frac{\partial J}{\partial \text{vec}(W)} = (g_1 \mathbf{x}^T \quad g_2 \mathbf{x}^T \quad \dots \quad g_C \mathbf{x}^T) + 2\lambda \text{vec}(W)^T$$

(where  $\mathbf{g} = \frac{\partial J}{\partial \mathbf{z}}$ ) from a vector ( $1 \times Cd$ ) back to a 2D matrix ( $C \times d$ ):

$$\frac{\partial J}{\partial W} = \begin{pmatrix} g_1 \mathbf{x}^T \\ g_2 \mathbf{x}^T \\ \vdots \\ g_C \mathbf{x}^T \end{pmatrix} + 2\lambda W = \mathbf{g}^T \mathbf{x}^T + 2\lambda W$$

# Aggregating the Gradient computations



**linear scoring function + SOFTMAX + cross-entropy loss + Regularization**

$$\mathbf{g} = \frac{\partial J}{\partial l} = 1$$

$$\mathbf{g} \leftarrow \mathbf{g} \frac{\partial l}{\partial \mathbf{p}} = \left( -\frac{\mathbf{y}^T}{\mathbf{y}^T \mathbf{p}} \right) \leftarrow \frac{\partial J}{\partial \mathbf{p}}$$

$$\mathbf{g} \leftarrow \mathbf{g} \frac{\partial \mathbf{p}}{\partial \mathbf{s}} = \mathbf{g} \left( \text{diag}(\mathbf{p}) - \mathbf{p}\mathbf{p}^T \right) \leftarrow \frac{\partial J}{\partial \mathbf{s}}$$


$$\mathbf{g} \leftarrow \mathbf{g} \frac{\partial \mathbf{s}}{\partial \mathbf{z}} = \mathbf{g} \mathbf{I}_C \leftarrow \frac{\partial J}{\partial \mathbf{z}}$$

Then

$$\frac{\partial J}{\partial \mathbf{b}} = \mathbf{g}$$

$$\frac{\partial J}{\partial \mathbf{W}} = \mathbf{g}^T \mathbf{x}^T + 2\lambda \mathbf{W}$$

# Aggregating the Gradient computations



linear scoring function + SOFTMAX + cross-entropy loss + Regularization

1. Let

$$\mathbf{g} = -\frac{\mathbf{y}^T}{\mathbf{y}^T \mathbf{p}} \left( \text{diag}(\mathbf{p}) - \mathbf{p}\mathbf{p}^T \right)$$

2. The gradient of  $J$  w.r.t. the bias vector is the  $1 \times d$  vector

$$\frac{\partial J}{\partial \mathbf{b}} = \mathbf{g}$$

3. The gradient of  $J$  w.r.t. the weight matrix  $W$  is the  $c \times d$  matrix

$$\frac{\partial J}{\partial W} = \mathbf{g}^T \mathbf{x}^T + 2\lambda W$$

# Gradient Computations for a mini-batch

- Have explicitly described the gradient computations for one training example  $(\mathbf{x}, y)$ .
- In general, want to compute the gradients of the cost function for a mini-batch  $\mathcal{D}$ .

$$\begin{aligned} J(\mathcal{D}, W, \mathbf{b}) &= L(\mathcal{D}, W, \mathbf{b}) + \lambda \|W\|^2 \\ &= \frac{1}{|\mathcal{D}|} \sum_{(\mathbf{x}, y) \in \mathcal{D}} l(\mathbf{x}, y, W, \mathbf{b}) + \lambda \|W\|^2 \end{aligned}$$

- The gradients we need to compute are

$$\frac{\partial J(\mathcal{D}, W, \mathbf{b})}{\partial W} = \frac{\partial L(\mathcal{D}, W, \mathbf{b})}{\partial W} + 2\lambda W = \frac{1}{|\mathcal{D}|} \sum_{(\mathbf{x}, y) \in \mathcal{D}} \frac{\partial l(\mathbf{x}, y, W, \mathbf{b})}{\partial W} + 2\lambda W$$

$$\frac{\partial J(\mathcal{D}, W, \mathbf{b})}{\partial \mathbf{b}} = \frac{\partial L(\mathcal{D}, W, \mathbf{b})}{\partial \mathbf{b}} = \frac{1}{|\mathcal{D}|} \sum_{(\mathbf{x}, y) \in \mathcal{D}} \frac{\partial l(\mathbf{x}, y, W, \mathbf{b})}{\partial \mathbf{b}}$$

# Gradient Computations for a mini-batch

## linear scoring function + SOFTMAX + cross-entropy loss + Regularization

- Compute gradients of  $l$  w.r.t.  $W$ ,  $\mathbf{b}$  for each  $(\mathbf{x}, y) \in \mathcal{D}^{(t)}$ :
  - Set all entries in  $\frac{\partial L}{\partial \mathbf{b}}$  and  $\frac{\partial L}{\partial W}$  to zero.
  - for  $(\mathbf{x}, y) \in \mathcal{D}^{(t)}$ 
    1. Let

$$\mathbf{g} = -\frac{\mathbf{y}^T}{\mathbf{y}^T \mathbf{p}} \left( \text{diag}(\mathbf{p}) - \mathbf{p}\mathbf{p}^T \right)$$

2. Add gradient of  $l$  w.r.t.  $\mathbf{b}$  computed at  $(\mathbf{x}, y)$

$$\frac{\partial L}{\partial \mathbf{b}} += \mathbf{g}$$

3. Add gradient of  $l$  w.r.t.  $W$  computed at  $(\mathbf{x}, y)$

$$\frac{\partial L}{\partial W} += \mathbf{g}^T \mathbf{x}^T$$

- Divide by the number of entries in  $\mathcal{D}^{(t)}$ :

$$\frac{\partial L}{\partial W} /= |\mathcal{D}^{(t)}|, \quad \frac{\partial L}{\partial \mathbf{b}} /= |\mathcal{D}^{(t)}|$$

- Add the gradient for the regularization term

$$\frac{\partial J}{\partial W} = \frac{\partial L}{\partial W} + 2\lambda W, \quad \frac{\partial J}{\partial \mathbf{b}} = \frac{\partial L}{\partial \mathbf{b}}$$